## FLIGHT SUMMARY REPORT

Flight Number: 97-009-05

Calendar/Julian Date: 22 September 1997 • 265

Sensor Package: Thermal Infrared Multispectral

Scanner (TIMS)

DoE Multispectral Scanner (MSS)

Area(s) Covered: Lewis and Clark County, Montana

Site 753

Investigator(s): Rowan, USGS Aircraft #: 799 Department of Energy

Cessna Citation

## SENSOR DATA

Accession #: Sensor ID #: 086 1268 Sensor Type: TIMS MSS Focal Length: --------Film Type: \_\_\_\_ Filtration: ----Spectral Band: f Stop: --------**Shutter Speed:** ----# of Frames: ----% Overlap: **Quality:** Good Good

Remarks:

# **Airborne Science and Applications Program**

The Airborne Science Branch at NASA's Dryden Flight Research Center, Edwards, California, operates two ER-2 high altitude aircraft in support of NASA earth science research. The ER-2s are used as readily deployable high altitude sensor platforms to collect remote sensing and in situ data on earth resources, celestial phenomena, atmospheric dynamics, and oceanic processes. Additionally, these aircraft are used for electronic sensor research and development and satellite investigative support.

The ER-2s are flown from various deployment sites in support of scientific research sponsored by NASA and other federal, state, university, and industry investigators. Data are collected from deployment sites in Kansas, Texas, Virginia, Florida, and Alaska. Cooperative international scientific projects have deployed the aircraft to sites in Great Britain, Australia, Chile, and Norway.

Photographic and digital imaging sensors are flown aboard the ER-2s in support of research objectives defined by the sponsoring investigators. High resolution mapping cameras and digital multispectral imaging sensors are utilized in a variety of configurations in the ER-2s' four pressurized experiment compartments. The following provides a description of the digital multispectral sensor(s) and camera(s) used for data collection during this flight.

#### **Department of Energy Remote Sensing Laboratory**

The NASA Airborne Science and Applications Program at Ames Research Center contracted with the Department of Energy Remote Sensing Laboratory (RSL) in Las Vegas, Nevada to fly the RSL Multispectral Scanner (MSS) and the NASA Thermal Infrared Multispectral Scanner (TIMS) over the desert southwest. The scanners were flown on the DOE Cessna Citation.

The Cessna Citation is a low and medium altitude, moderate speed aircraft. It can operate from 4,000 to 35,000 feet above sea level at speeds between 135 and 225 knots. There are two instrument ports in the aircraft. The RSL 1268 Multispectral Scanner was mounted over the aft port and the NASA Thermal Infrared Multispectral Scanner was mounted over the forward port.

#### RSL Daedalus 1268 MSS

The DOE Multispectral Scanner simulates the spectral characteristics the Thematic Mapper (TM) multispectral scanners orbiting on Landsat 4 and Landsat 5. The seven TM bands are replicated with the MSS and four additional bands of discrete wavelengths are acquired. THE MSS acquires TM band six (thermal data) as two bands in low and high gain settings. The scanner is configured as follows:

Daedalus Channel	TM Band	Wavelength, mm
1	A	0.42 - 0.45
2	1	0.45 - 0.52
3	2	0.52 - 0.60
4	В	0.60 - 0.62
5	3	0.63 - 0.69
6	C	0.69 - 0.75
7	4	0.75 - 0.90

8	D	0.91 - 1.05
9	5	1.55 - 1.75
10	7	2.08 - 2.35
11	6	8.5 - 12.5 low gain
12	6	8.5 - 12.5 high gain

Sensor/aircraft parameters are as follows:

IFOV: 2.5 mrad Total Scan Angle: 86° Pixels/Scan Line: 716

Scan Rate: 12.5/25/50/100 scans/second

# **Thermal Infrared Multispectral Scanner**

The Thermal Infrared Multispectral Scanner (TIMS) is a multispectral scanning system using a dispersive grating and a six element mercury cadmium telluride detector array to produce six discrete channels in the 8.2 mm to 12.2 mm region.

<u>Channel</u>	Wavelength, mm	<u>NET</u>
1	8.2 - 8.6	< 0.30 C
2	8.6 - 9.0	< 0.30 C
3	9.0 - 9.4	< 0.30 C
4	9.4 - 10.2	< 0.30 C
5	10.2 - 11.2	< 0.30 C
6	11.2 - 12.2	$< 0.30  {\rm C}$

Sensor/aircraft parameters are as follows:

IFOV: 2.5 mrad

Ground Resolution: 163 feet (50 meters) at 65,000 feet

Total Scan Angle: 76.56°

Swath Width: 16.9 nmi (31.3 km) at 65,000 feet

Pixels/Scan Line: 638

Scan Rate: 7.3 (scans/second)
Ground Speed: 400 kts. (206 m/second)

Information on data tape format, logical record format, and scanner calibration data may be obtained from the Aircraft Data Facility, NASA-Ames Research Center, Mail Stop 240-6, Moffett Field, California 94035-1000 (Telephone: 650-604-6252).

#### TIMS FLIGHT DATA FLIGHT NUMBER: 97-009-05

	Site	Line	Run	Act time begin		Actual scanline begin end	Altitude feet/meter	Scan Speed (rps)	total G o o d scanlines	total Interpolated scanlines	total Repeated scanlines
1.	753	7	1	17:54:59.0	17:58:08.2	50213 54942	10500/ 3200	25.00	4730	0	0
2.	753	6	1	18:06:36.6	18:09:36.8	67568 72073	10500/ 3200	25.00	4506	0	0
3.	753	5	1	18:18:03.7	18:20:54.3	84658 88922	10500/ 3200	25.00	4265	0	0
4.	753	5	2	18:29:11.3	18:32:16.8	101265 105904	10500/ 3200	25.00	4640	0	0
5.	753	4	1	18:40:39.3	18:43:43.8	118376 122988	10500/ 3200	25.00	4613	0	0
6.	753	3	1	18:52:03.0	18:55:11.7	135393 140111	10500/ 3200	25.00	4719	0	0
7.	753	2	1	19:03:16.0	19:06:22.1	152129 156782	10500/ 3200	25.00	4654	0	0
8.	753	1	1	19:14:19.5	19:17:20.0	168635 173148	10500/ 3200	25.00	4514	0	0

Notes: Site 753 Lewis and Clark County Montana

# DOE DAEDALUS TMS FLIGHT DATA FLIGHT NUMBER: 97-009-05

	Site	Line	Run	Act time begin		scan	ual nline end	Altitude feet/mete		total G o o d scanlines	total Interpolated scanlines	total Repeated scanlines
1.	753	7	1	17:54:59.0	17:58:08.8	45008	49752	10500/ 320	0 25.00	4745	0	0
2.	753	6	1	18:06:36.0	18:09:42.7	62279	66946	10500/ 320	0 25.00	4668	0	0
3.	753	5	1	18:18:07.8	18:20:59.0	79574	83853	10500/ 320	0 25.00	4280	0	0
4.	753	5	2	18:29:14.6	18:32:20.6	96243	100895	10500/ 320	0 25.00	4653	0	0
5.	753	4	1	18:40:41.5	18:43:46.6	113416	118043	10500/ 320	0 25.00	4628	0	0
6.	753	3	1	18:52:04.5	18:55:13.9	130492	135226	10500/ 320	0 25.00	4735	0	0
7.	753	2	1	19:03:16.4	19:06:23.2	147289	151958	10500/ 320	0 25.00	4670	0	0
8.	753	1	1	19:14:19.1	19:17:20.0	163856	168380	10500/ 320	0 25.00	4525	0	0

Notes: Site 753 Lewis and Clark County Montana



